



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

Ferycon Labs, S.A. de C.V. (Instrulab)
Blvd. Peña Flor, No. 1102, Novatec Busines Park Nave B8, Ciudad del Sol
Querétaro, Querétaro, México. C.P. 76116

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Dimensional Inspection
(As detailed in the supplement)

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen
President

Initial Accreditation Date:

August 13, 2014

Issue Date:

October 21, 2022

Expiration Date:

January 31, 2025

Accreditation No.:

78970

Certificate No.:

L22-708

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: www.pjlabs.com



Certificate of Accreditation: Supplement

Ferycon Labs, S.A. de C.V. (Instrulab)

Blvd. Peña Flor, No. 1102, Novatec Busines Park Nave B8, Ciudad del Sol
Querétaro, Querétaro, México. C.P. 76116
Contact Name: Fernando Briseño Phone: 442-403-5892

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Dimensional Inspection ^F	Dimensional Artifacts 3-Axis Volumetric and Linear Displacement	Measurement of Parts Geometrically Dimensioned and Tolerance (GD&T)	ASME Y 14.5 CMM	X= 700 mm Y= 1 000 mm Z= 600 mm
			ASME Y 14.5 CMM ZCat	X= 700 mm Y= 700 mm Z= 250 mm
			ASME Y 14.5 Vision System Machine	0° to 360° X= 200 mm Y= 250 mm Z= 100 mm

- The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer^F would mean that the laboratory performs this testing at its fixed location.

